

Pari-GP reference card

(PARI-GP version 2.9.0)

Note: optional arguments are surrounded by braces {}.

To start the calculator, type its name in the terminal: **gp**

To exit **gp**, type **quit**, **\q**, or **<C-D>** at prompt.

Help

describe function	?function
extended description	??keyword
list of relevant help topics	???pattern
name of GP-1.39 function f in GP-2.*	whatnow(f)

Input/Output

previous result, the result before	%, %', %'', etc.
n -th result since startup	% n
separate multiple statements on line	;
extend statement on additional lines	\
extend statements on several lines	{seq ₁ ; seq ₂ ;}
comment	/* ... */
one-line comment, rest of line ignored	\\ ...

Metacommands & Defaults

set default d to val	default({ d },{ val })
toggle timer on/off	#
print time for last result	##
print defaults	\d
set debug level to n	\g n
set memory debug level to n	\gm n
set n significant digits / bits	\p n , \pb n
set n terms in series	\ps n
quit GP	\q
print the list of PARI types	\t
print the list of user-defined functions	\u
read file into GP	\r filename

Debugger / break loop

get out of break loop	break or <C-D>
go up/down n frames	dbg_up({ n }), dbg_down
set break point	breakpoint()
examine object o	dbg_x(o)
current error data	dbg_err()
number of objects on heap and their size	getheap()
total size of objects on PARI stack	getstack()

PARI Types & Input Formats

t_INT . Integers; hex, binary	± 31 ; $\pm 0x1F$, $\pm 0b101$
t_REAL . Reals	± 3.14 , 6.022 E23
t_INTMOD . Integers modulo m	Mod(n , m)
t_FRAC . Rational Numbers	n/m
t_FFELT . Elt in finite field F_q	ffgen(q)
t_COMPLEX . Complex Numbers	$x + y * I$
t_PADIC . p -adic Numbers	$x + O(p^k)$
t_QUAD . Quadratic Numbers	$x + y * \text{quadgen}(D)$
t_POLMOD . Polynomials modulo g	Mod(f , g)
t_POL . Polynomials	$a * x^n + \dots + b$
t_SER . Power Series	$f + O(x^k)$
t_RFRAC . Rational Functions	f/g
t_QFI / t_QFR . Imag/Real binary quad. form	Qfb($a, b, c, \{d\}$)
t_VEC / t_COL . Row/Column Vectors	[x, y, z], [x, y, z]-
t_VEC integer range	[1..10]

t_VECSMALL . Vector of small ints	Vecsmall([x, y, z])
t_MAT . Matrices	[$a, b; c, d$]
t_LIST . Lists	List([x, y, z])
t_STR . Strings	"abc"
t_INFINITY . $\pm\infty$	+oo, -oo

Reserved Variable Names

$\pi = 3.14\dots$, $\gamma = 0.57\dots$, $C = 0.91\dots$	Pi, Euler, Catalan
square root of -1	I
Landau's big-oh notation	O

Information about an Object

PARI type of object x	type(x)
length of x / size of x in memory	# x , sizebyte(x)
real precision / bit precision of x	precision(x), bitprecision
p -adic, series prec. of x	padicprec(x), serprec

Operators

basic operations	+, -, *, /, ^, sqr
$i=i+1$, $i=i-1$, $i=i*j$, ...	i++, i--, i*=j,...
euclidean quotient, remainder	$x \backslash y$, $x \backslash y$, $x \% y$, divrem(x, y)
shift x left or right n bits	$x << n$, $x >> n$ or shift($x, \pm n$)
multiply by 2^n	shiftmul(x, n)
comparison operators	<=, <, >=, >, ==, !=, ==, lex, cmp
boolean operators (or, and, not)	, &&, !
bit operations	bitand, bitneg, bitor, bitxor, bitnegimply
sign of $x = -1, 0, 1$	sign(x)
maximum/minimum of x and y	max, min(x, y)
derivative of f	f'
differential operator	diffop($f, v, d, \{n = 1\}$)
quote operator (formal variable)	' x
assignment	$x = value$
simultaneous assignment $x \leftarrow v_1, y \leftarrow v_2$	[x, y] = v

Select Components

n -th component of x	component(x, n)
n -th component of vector/list x	$x[n]$
components $a, a + 1, \dots, b$ of vector x	$x[a..b]$
(m, n) -th component of matrix x	$x[m, n]$
row m or column n of matrix x	$x[m,]$, $x[, n]$
numerator/denominator of x	numerator(x), denominator

Random Numbers

random integer/prime in $[0, N[$	random(N), randomprime
get/set random seed	getrand, setrand(s)

Conversions

to vector, matrix, vec. of small ints	Col/Vec, Mat, Vecsmall
to list, set, map, string	List, Set, Map, Str
create PARI object ($x \bmod y$)	Mod(x, y)
make x a polynomial of v	Pol($x, \{v\}$)
as Pol, etc., starting with constant term	Polrev, Vecrev, Colrev
make x a power series of v	Ser($x, \{v\}$)
string from bytes / from format+args	Strchr, Strprintf
TeX string	Strtex(x)
convert x to simplest possible type	simplify(x)
object x with real precision n	precision(x, n)
object x with bit precision n	bitprecision(x, n)
set precision to p digits in dynamic scope	localprec(p)
set precision to p bits in dynamic scope	localbitprec(p)

Conjugates and Lifts

conjugate of a number x	conj(x)
norm of x , product with conjugate	norm(x)
L^p norm of x (L^∞ if no p)	normlp($x, \{p\}$)
square of L^2 norm of x	norml2(x)
lift of x from Mods and p -adics	lift, centerlift(x)
recursive lift	liftall
lift all t_INT and t_PADIC (\rightarrow t_INT)	liftint
lift all t_POLMOD (\rightarrow t_POL)	liftpol

Lists, Sets & Maps

Sets (= row vector with strictly increasing entries w.r.t. **cmp**)

intersection of sets x and y	setintersect(x, y)
set of elements in x not belonging to y	setminus(x, y)
union of sets x and y	setunion(x, y)
does y belong to the set x	setsearch($x, y, \{flag\}$)
set of all $f(x, y)$, $x \in X$, $y \in Y$	setbinop(f, X, Y)
is x a set ?	setisset(x)

Lists. create empty list: $L = \text{List}()$

append x to list L	listput($L, x, \{i\}$)
remove i -th component from list L	listpop($L, \{i\}$)
insert x in list L at position i	listinsert(L, x, i)
sort the list L in place	listsort($L, \{flag\}$)

Maps. create empty dictionary: $M = \text{Map}()$

attach value v to key k	mapput(M, k, v)
recover value attach to key k or error	mapget(M, k)
is key k in the dict ? (set v to $M(k)$)	mapisdefined($M, k, \{\&v\}$)
remove k from map domain	mapdelete(M, k)

GP Programming

User functions and closures

x, y are formal parameters; y defaults to **Pi** if parameter opitted; z, t are local variables (lexical scope), z initialized to 1.

```
fun(x, y=Pi) = my(z=1, t); seq
fun = (x, y=Pi) -> my(z=1, t); seq
attach a help message to f      addhelp(f)
undefine symbol s (also kills help)  kill(s)
Control Statements ( $X$ : formal parameter in expression  $seq$ )
if  $a \neq 0$ , evaluate  $seq_1$ , else  $seq_2$       if( $a, \{seq_1\}, \{seq_2\}$ )
eval.  $seq$  for  $a \leq X \leq b$                   for( $X = a, b, seq$ )
...for primes  $a \leq X \leq b$                   forprime( $X = a, b, seq$ )
...for composites  $a \leq X \leq b$               forcomposite( $X = a, b, seq$ )
...for  $a \leq X \leq b$  stepping  $s$               forstep( $X = a, b, s, seq$ )
...for  $X$  dividing  $n$                          fordiv( $n, X, seq$ )
multivariable for, lex ordering             forvec( $X = v, seq$ )
loop over partitions of  $n$                    forpart( $p = n, seq$ )
loop over vectors  $v$ ,  $q(v) \leq B$ ;  $q > 0$        forqfvec( $v, q, b, seq$ )
loop over  $H < G$  finite abelian group        forsubgroup( $H = G$ )
```

evaluate seq until $a \neq 0$	until(a, seq)
while $a \neq 0$, evaluate seq	while(a, seq)
exit n innermost enclosing loops	break({ n })
start new iteration of n -th enclosing loop	next({ n })
return x from current subroutine	return({ x })

Exceptions, warnings

raise an exception / warn	error(), warning()
type of error message E	errname(E)
try seq_1 , evaluate seq_2 on error	iferr(seq_1, E, seq_2)

Functions with closure arguments / results

select from v according to f `select(f, v)`
apply f to all entries in v `apply(f, v)`
evaluate $f(a_1, \dots, a_n)$ `call(f, a)`
evaluate $f(\dots f(f(a_1, a_2), a_3) \dots, a_n)$ `fold(f, a)`
calling function as closure `self()`

Sums & Products

sum $X = a$ to $X = b$, initialized at x `sum($X = a, b, expr, \{x\}$)`
sum entries of vector v `vecsum(v)`
sum $expr$ over divisors of n `sumdiv($n, X, expr$)`
... assuming $expr$ multiplicative `sumdivmult($n, X, expr$)`
product $a \leq X \leq b$, initialized at x `prod($X = a, b, expr, \{x\}$)`
product over primes $a \leq X \leq b$ `prodeuler($X = a, b, expr$)`

Sorting

sort x by k -th component `vecsort($x, \{k\}, \{fl = 0\}$)`
min. m of x ($m = x[i]$), max. `vecmin($x, \{\&i\}$), vecmax`
does y belong to x , sorted wrt. f `vecsearch($x, y, \{f\}$)`

Input/Output

print with/without $\backslash n$, T_EX format `print, print1, printtex`
print fields with separator `printsep(sep, \dots), printsep1`
formatted printing `printf()`
write $args$ to file `write, write1, writetex($file, args$)`
write x in binary format `writebin($file, x$)`
read file into GP `read($\{file\}$)`
... return as vector of lines `readvec($\{file\}$)`
... return as vector of strings `readstr($\{file\}$)`
read a string from keyboard `input()`

Timers

CPU time in ms and reset timer `gettime()`
CPU time in ms since gp startup `getabstime()`
time in ms since UNIX Epoch `getwalltime()`
timeout command after s seconds `alarm($s, expr$)`

Interface with system

allocates a new stack of s bytes `allocatemem($\{s\}$)`
alias old to new `alias(new, old)`
install function from library `install($f, code, \{gpf\}, \{lib\}$)`
execute system command a `system(a)`
as above, feed result to GP `extern(a)`
as above, return GP string `externstr(a)`
get \$VAR from environment `getenv("VAR")`
expand env. variable in string `Strexpand(x)`

Parallel evaluation

These functions evaluate their arguments in parallel (pthreads or MPI); args. must not access global variables and must be free of side effects. Enabled if threading engine is not *single* in gp header.
evaluate f on $x[1], \dots, x[n]$ `parapply(f, x)`
evaluate closures $f[1], \dots, f[n]$ `pareval(f)`
as **select** `parselect($f, A, \{flag\}$)`
as **sum** `parsum($i = a, b, expr, \{x\}$)`
as **vector** `parvector($n, i, \{expr\}$)`
eval f for $i = a, \dots, b$ `parfor($i = a, \{b\}, f, \{r\}, \{f_2\}$)`
... for p prime in $[a, b]$ `parforprime($p = a, \{b\}, f, \{r\}, \{f_2\}$)`
... multivariate `parforvec($X = v, f, \{r\}, \{f_2\}, \{flag\}$)`
declare x as inline (allows to use as global) `inline(x)`
stop inlining `uninline()`

Pari-GP reference card

(PARI-GP version 2.9.0)

Linear Algebra

dimensions of matrix x `matsize(x)`
concatenation of x and y `concat($x, \{y\}$)`
extract components of x `vecextract($x, y, \{z\}$)`
transpose of vector or matrix x `mattranspose(x)` or $x \sim$
adjoint of the matrix x `matadjoint(x)`
eigenvectors/values of matrix x `mateigen(x)`
characteristic/minimal polynomial of x `charpoly(x), minpoly`
trace/determinant of matrix x `trace(x), matdet`
Frobenius form of x `matfrobenius(x)`
QR decomposition `matqr(x)`
apply **matqr**'s transform to v `mathouseholder(Q, v)`

Constructors & Special Matrices

$\{g(x): x \in v \text{ s.t. } f(x)\}$ `[$g(x) \mid x \leftarrow v, f(x)$]`
 $\{x: x \in v \text{ s.t. } f(x)\}$ `[$x \mid x \leftarrow v, f(x)$]`
 $\{g(x): x \in v\}$ `[$g(x) \mid x \leftarrow v$]`
row vec. of $expr$ eval'ed at $1 \leq i \leq n$ `vector($n, \{i\}, \{expr\}$)`
col. vec. of $expr$ eval'ed at $1 \leq i \leq n$ `vectorv($n, \{i\}, \{expr\}$)`
vector of small ints `vectorsmall($n, \{i\}, \{expr\}$)`
 $[c, c \cdot x, \dots, c \cdot x^n]$ `powers($x, n, \{c = 1\}$)`
matrix $1 \leq i \leq m, 1 \leq j \leq n$ `matrix($m, n, \{i\}, \{j\}, \{expr\}$)`
define matrix by blocks `matconcat(B)`
diagonal matrix with diagonal x `matdiagonal(x)`
is x diagonal? `matisdiagonal(x)`
 $x \cdot \text{matdiagonal}(d)$ `matmuldiagonal(x, d)`
 $n \times n$ identity matrix `matid(n)`
Hessenberg form of square matrix x `mathess(x)`
 $n \times n$ Hilbert matrix $H_{ij} = (i + j - 1)^{-1}$ `mathilbert(n)`
 $n \times n$ Pascal triangle `matpascal($n - 1$)`
companion matrix to polynomial x `matcompanion(x)`
Sylvester matrix of x `polsylvestermatrix(x)`

Gaussian elimination

kernel of matrix x `matker($x, \{flag\}$)`
intersection of column spaces of x and y `matintersect(x, y)`
solve $M * X = B$ (M invertible) `matsolve(M, B)`
as solve, modulo D (col. vector) `matsolvemod(M, D, B)`
one sol of $M * X = B$ `matinverseimage(M, B)`
basis for image of matrix x `matimage(x)`
columns of x *not* in **matimage** `matimagecompl(x)`
supplement columns of x to get basis `matsupplement(x)`
rows, cols to extract invertible matrix `matindexrank(x)`
rank of the matrix x `matrank(x)`

Lattices & Quadratic Forms

Quadratic forms

evaluate ${}^t x Q y$ `qfeval($\{Q = id\}, x, y$)`
evaluate ${}^t x Q x$ `qfeval($\{Q = id\}, x$)`
signature of quad form ${}^t y * x * y$ `qfsign(x)`
decomp into squares of ${}^t y * x * y$ `qfgaussred(x)`
eigenvalues/vectors for real symmetric x `qfjacobi(x)`

HNF and SNF

upper triangular Hermite Normal Form `mathnf(x)`
HNF of x where d is a multiple of $\det(x)$ `mathnfmod(x, d)`
multiple of $\det(x)$ `matdetint(x)`
HNF of $(x \mid \text{diagonal}(D))$ `mathnfmodid(x, D)`
elementary divisors of x `mathsnf(x)`
elementary divisors of $\mathbf{Z}[a]/(f'(a))$ `poldiscreduced(f)`
integer kernel of x `matkerint(x)`
 \mathbf{Z} -module \leftrightarrow \mathbf{Q} -vector space `matrixqz(x, p)`

Lattices

LLL-algorithm applied to columns of x `qflll($x, \{flag\}$)`
... for Gram matrix of lattice `qflllgram($x, \{flag\}$)`
find up to m sols of **qfnorm**(x, y) $\leq b$ `qfminim(x, b, m)`
 $v, v[i] :=$ number of y s.t. **qfnorm**(x, y) = i `qfrep($x, B, \{flag\}$)`
perfection rank of x `qfperfection(x)`
find isomorphism between q and Q `qfism(q, Q)`
precompute for isomorphism test with q `qfisminit(q)`
automorphism group of q `qfauto(q)`
convert **qfauto** for GAP/Magma `qfautoexport($G, \{flag\}$)`
orbits of V under $G \subset \text{GL}(V)$ `qforbits(G, V)`

Polynomials & Rational Functions

all defined polynomial variables `variables()`
get var. of highest priority (higher than v) `varhigher($name, \{v\}$)`
... of lowest priority (lower than v) `varlower($name, \{v\}$)`

Coefficients, variables and basic operators

degree of f `poldegree(f)`
coeff. of degree n of f , leading coeff. `polcoeff(f, n), pollead`
main variable / all variables in f `variable(f), variables(f)`
replace x by y in f `subst(f, x, y)`
evaluate f replacing vars by their value `eval(f)`
replace polynomial expr. $T(x)$ by y in f `substpol(f, T, y)`
replace x_1, \dots, x_n by y_1, \dots, y_n in f `substvec(f, x, y)`
reciprocal polynomial $x^{\deg f} f(1/x)$ `polrecip(f)`
gcd of coefficients of f `content(f)`
derivative of f w.r.t. x `deriv($f, \{x\}$)`
formal integral of f w.r.t. x `intformal($f, \{x\}$)`
formal sum of f w.r.t. x `sumformal($f, \{x\}$)`

Constructors & Special Polynomials

interpolating pol. eval. at a `polinterpolate($X, \{Y\}, \{a\}$)`
 $P_n, T_n/U_n, H_n$ `pollegendre, polchebyshev, polhermite`
 n -th cyclotomic polynomial Φ_n `polcyclo($n, \{v\}$)`
return n if $f = \Phi_n$, else 0 `poliscyclo(f)`
is f a product of cyclotomic polynomials? `poliscycloprod(f)`
Zagier's polynomial of index (n, m) `polzagier(n, m)`

Resultant, elimination

discriminant of polynomial f `poldisc(f)`
resultant $R = \text{Res}_v(f, g)$ `polresultant($f, g, \{v\}$)`
 $[u, v, R], xu + yv = \text{Res}_v(f, g)$ `polresultanttext($x, y, \{v\}$)`
solve Thue equation $f(x, y) = a$ `thue($t, a, \{sol\}$)`
initialize t for Thue equation solver `thueinit(f)`

Based on an earlier version by Joseph H. Silverman

August 2016 v2.30. Copyright © 2016 K. Belabas

Permission is granted to make and distribute copies of this card provided the copyright and this permission notice are preserved on all copies.

Send comments and corrections to (Karim.Belabas@math.u-bordeaux.fr)

Pari-GP reference card

(PARI-GP version 2.9.0)

Roots and Factorization

complex roots of f	<code>polroots(f)</code>
number of real roots of f (in $[a, b]$)	<code>polsturm($f, \{[a, b]\}$)</code>
real roots of f (in $[a, b]$)	<code>polrootsreal($f, \{[a, b]\}$)</code>
symmetric powers of roots of f up to n	<code>polsym(f, n)</code>
Graeffe transform of f , $g(x^2) = f(x)f(-x)$	<code>polgraeffe(f)</code>
factor f	<code>factor(f)</code>
factor f mod p / roots	<code>factormod(f, p), polrootsmod</code>
... using Cantor-Zassenhaus	<code>factorcantor(f, p)</code>
factor f over \mathbf{F}_{p^a} / roots	<code>factorff(f, p, a), polrootsff</code>
factor f over \mathbf{Q}_p / roots	<code>factorpadic(f, p, r), polrootspadic</code>
cyclotomic factors of $f \in \mathbf{Q}[X]$	<code>polcyclofactors(f)</code>
find irreducible $T \in \mathbf{F}_p[x]$, $\deg T = n$	<code>ffinit($p, n, \{x\}$)</code>
$\#\{\text{monic irred. } T \in \mathbf{F}_q[x], \deg T = n\}$	<code>ffnbirred(q, n)</code>
p -adic root of f congruent to a mod p	<code>padicappr(f, a)</code>
Newton polygon of f for prime p	<code>newtonpoly(f, p)</code>
Hensel lift $A/\text{lc}(A) = \prod_i B[i] \bmod p^e$	<code>polhensellift(A, B, p, e)</code>
extensions of \mathbf{Q}_p of degree N	<code>padicfields(p, N)</code>

Formal & p-adic Series

truncate power series or p -adic number	<code>truncate(x)</code>
valuation of x at p	<code>valuation(x, p)</code>
Dirichlet and Power Series	
Taylor expansion around 0 of f w.r.t. x	<code>taylor(f, x)</code>
$\sum a_k b_k t^k$ from $\sum a_k t^k$ and $\sum b_k t^k$	<code>serconvol(a, b)</code>
$f = \sum a_k t^k$ from $\sum (a_k/k!) t^k$	<code>serlaplace(f)</code>
reverse power series F so $F(f(x)) = x$	<code>serreverse(f)</code>
Dirichlet series multiplication / division	<code>dirmul, dirdiv(x, y)</code>
Dirichlet Euler product (b terms)	<code>direuler($p = a, b, expr$)</code>

Transcendental and p -adic Functions

real, imaginary part of x	<code>real(x), imag(x)</code>
absolute value, argument of x	<code>abs(x), arg(x)</code>
square/nth root of x	<code>sqrt(x), sqrtn($x, n, \{&z\}$)</code>
trig functions	<code>sin, cos, tan, cotan, sinc</code>
inverse trig functions	<code>asin, acos, atan</code>
hyperbolic functions	<code>sinh, cosh, tanh, cotanh</code>
inverse hyperbolic functions	<code>asinh, acosh, atanh</code>
$\log(x)$, e^x , $e^x - 1$	<code>log, exp, expm1</code>
Euler Γ function, $\log \Gamma$, Γ'/Γ	<code>gamma, lngamma, psi</code>
half-integer gamma function $\Gamma(n+1/2)$	<code>gammah(n)</code>
Riemann's zeta $\zeta(s) = \sum n^{-s}$	<code>zeta(s)</code>
multiple zeta value (MZV), $\zeta(s_1, \dots, s_k)$	<code>zetamul(s)</code>
incomplete Γ function ($y = \Gamma(s)$)	<code>incgam($s, x, \{y\}$)</code>
complementary incomplete Γ	<code>incgamc(s, x)</code>
exponential integral $\int_x^\infty e^{-t}/t dt$	<code>eint1(x)</code>
error function $2/\sqrt{\pi} \int_x^\infty e^{-t^2} dt$	<code>erfc(x)</code>
dilogarithm of x	<code>dilog(x)</code>
m -th polylogarithm of x	<code>polylog($m, x, \{flag\}$)</code>
U -confluent hypergeometric function	<code>hyperu(a, b, u)</code>
Bessel $J_n(x)$, $J_{n+1/2}(x)$	<code>besselj(n, x), besseljh(n, x)</code>
Bessel I_ν , K_ν , H_ν^1 , H_ν^2 , N_ν	<code>(bessel)i, k, h1, h2, n</code>
Lambert W : x s.t. $xe^x = y$	<code>lambertw(y)</code>
Teichmuller character of p -adic x	<code>teichmuller(x)</code>

Iterations, Sums & Products

Numerical integration for meromorphic functions

Behaviour at endpoint for Double Exponential methods: either a scalar ($a \in \mathbf{C}$, regular) or $\pm\infty$ (decreasing at least as x^{-2}) or $(x-a)^{-\alpha}$ singularity	<code>[a, α]</code>
exponential decrease $e^{-\alpha x }$	<code>$[\pm\infty, \alpha]$, $\alpha > 0$</code>
slow decrease $ x ^\alpha$	<code>$\dots \alpha < -1$</code>
oscillating as $\cos(kx)$	<code>$\alpha = k\mathbf{I}$, $k > 0$</code>
oscillating as $\sin(kx)$	<code>$\alpha = -k\mathbf{I}$, $k > 0$</code>
numerical integration	<code>intnum($x = a, b, f, \{T\}$)</code>
weights T for intnum	<code>intnuminit($a, b, \{m\}$)</code>
weights T incl. kernel K	<code>intfuncinit($a, b, K, \{m\}$)</code>
integrate $(2i\pi)^{-1}f$ on circle $ z-a = R$	<code>intcirc($x = a, R, f, \{T\}$)</code>

Other integration methods

n -point Gauss-Legendre	<code>intnumgauss($x = a, b, f, \{n\}$)</code>
weights for n -point Gauss-Legendre	<code>intnumgaussinit($\{n\}$)</code>
Romberg integration (low accuracy)	<code>intnumromb($x = a, b, f, \{flag\}$)</code>

Numerical summation

sum of series $f(n)$, $n \geq a$ (low accuracy)	<code>suminf($n = a, expr$)</code>
sum of alternating/positive series	<code>sumalt, sumpos</code>
sum of series using Euler-Maclaurin	<code>sumnum($n = a, f, \{T\}$)</code>
weights for sumnum, a as in DE	<code>sumnuminit($\{\infty, a\}$)</code>
sum of series by Monien summation	<code>sumnummonien($n = a, f, \{T\}$)</code>
weights for sumnummonien	<code>sumnummonieninit($\{\infty, a\}$)</code>

Products

product $a \leq X \leq b$, initialized at x	<code>prod($X = a, b, expr, \{x\}$)</code>
product over primes $a \leq X \leq b$	<code>prodeuler($X = a, b, expr$)</code>
infinite product $a \leq X \leq \infty$	<code>prodinf($X = a, expr$)</code>

Other numerical methods

real root of f in $[a, b]$; bracketed root	<code>solve($X = a, b, f$)</code>
... by interval splitting	<code>solvestep($X = a, b, f, \{flag = 0\}$)</code>
limit of $f(t)$, $t \rightarrow \infty$	<code>limitnum($f, \{k\}, \{\alpha\}$)</code>
asymptotic expansion of f at ∞	<code>asymnum($f, \{k\}, \{\alpha\}$)</code>
numerical derivation w.r.t x : $f'(a)$	<code>derivnum($x = a, f$)</code>
evaluate continued fraction F at t	<code>contfraceval($F, t, \{L\}$)</code>
power series to cont. fraction (L terms)	<code>contfracinit($S, \{L\}$)</code>
Padé approximant (deg. denom. $\leq B$)	<code>bestapprPade($S, \{B\}$)</code>

Elementary Arithmetic Functions

vector of binary digits of $ x $	<code>binary(x)</code>
bit number n of integer x	<code>bittest(x, n)</code>
Hamming weight of integer x	<code>hammingweight(x)</code>
digits of integer x in base B	<code>digits($x, \{B = 10\}$)</code>
sum of digits of integer x in base B	<code>sumdigits($x, \{B = 10\}$)</code>
integer from digits	<code>fromdigits($v, \{B = 10\}$)</code>
ceiling/floor/fractional part	<code>ceil, floor, frac</code>
round x to nearest integer	<code>round($x, \{&e\}$)</code>
truncate x	<code>truncate($x, \{&e\}$)</code>
gcd/LCM of x and y	<code>gcd(x, y), lcm(x, y)</code>
gcd of entries of a vector/matrix	<code>content(x)</code>

Primes and Factorization

extra prime table	<code>addprimes()</code>
add primes in v to prime table	<code>addprimes(v)</code>
remove primes from prime table	<code>removeprimes(v)</code>
Chebyshev $\pi(x)$, n -th prime p_n	<code>primepi(x), prime(n)</code>
vector of first n primes	<code>primes(n)</code>
smallest prime $\geq x$	<code>nextprime(x)</code>
largest prime $\leq x$	<code>precprime(x)</code>
factorization of x	<code>factor($x, \{lim\}$)</code>
... selecting specific algorithms	<code>factorint($x, \{flag = 0\}$)</code>
$n = df^2$, d squarefree/fundamental	<code>core($n, \{fl\}$), coredisc</code>
recover x from its factorization	<code>factorback($f, \{e\}$)</code>
$x \in \mathbf{Z}$, $ x \leq X$, $\gcd(N, P(x)) \geq N$	<code>zncoppersmith($P, N, X, \{B\}$)</code>

Divisors and multiplicative functions

number of prime divisors $\omega(n)$ / $\Omega(n)$	<code>omega(n), bigomega</code>
divisors of n / number of divisors $\tau(n)$	<code>divisors(n), numdiv</code>
sum of (k -th powers of) divisors of n	<code>sigma($n, \{k\}$)</code>
Möbius μ -function	<code>moebius(x)</code>
Ramanujan's τ -function	<code>ramanujantau(x)</code>

Combinatorics

factorial of x	<code>$x!$ or factorial(x)</code>
binomial coefficient $\binom{x}{y}$	<code>binomial(x, y)</code>
Bernoulli number B_n as real/rational	<code>bernreal(n), bernfrac</code>
Bernoulli polynomial $B_n(x)$	<code>bernpol($n, \{x\}$)</code>
n -th Fibonacci number	<code>fibonacci(n)</code>
Stirling numbers $s(n, k)$ and $S(n, k)$	<code>stirling($n, k, \{flag\}$)</code>
number of partitions of n	<code>numbpart(n)</code>
k -th permutation on n letters	<code>numtoperm(n, k)</code>
convert permutation to (n, k) form	<code>permtonum(v)</code>

Multiplicative groups $(\mathbf{Z}/N\mathbf{Z})^*$, \mathbf{F}_q^*

Euler ϕ -function	<code>eulerphi(x)</code>
multiplicative order of x (divides ϕ)	<code>znorder($x, \{o\}$), fforder</code>
primitive root mod q / $x \bmod q$	<code>znprimroot(q), fprimroot(x)</code>
structure of $(\mathbf{Z}/n\mathbf{Z})^*$	<code>znstar(n)</code>
discrete logarithm of x in base g	<code>znlog($x, g, \{o\}$), fflag</code>
Kronecker-Legendre symbol $\left(\frac{x}{y}\right)$	<code>kronecker(x, y)</code>
quadratic Hilbert symbol (at p)	<code>hilbert($x, y, \{p\}$)</code>

Miscellaneous

integer square / n -th root of x	<code>sqrtint(x), sqrtntint(x, n)</code>
largest integer e s.t. $b^e \leq b$, $e = \lfloor \log_b(b) \rfloor$	<code>logint($x, b, \{&z\}$)</code>
CRT: solve $z \equiv x$ and $z \equiv y$	<code>chinese(x, y)</code>
minimal u, v so $xu + yv = \gcd(x, y)$	<code>gcdext(x, y)</code>
continued fraction of x	<code>contfrac($x, \{b\}, \{lmax\}$)</code>
last convergent of continued fraction x	<code>contfracpnqn(x)</code>
rational approximation to x (den. $\leq B$)	<code>bestappr($x, \{B\}k$)</code>

Characters

Let $cyc = [d_1, \dots, d_k]$ represent an abelian group $G = \oplus (\mathbf{Z}/d_j\mathbf{Z}) \cdot g_j$ or any structure G affording a `.cyc` method; e.g. `idealstar(,g)` for Dirichlet characters. A character χ is coded by $[c_1, \dots, c_k]$ such that $\chi(g_j) = e(n_j/d_j)$.

$\chi \cdot \psi$; χ^{-1} ; $\chi \cdot \psi^{-1}$	<code>charmul, charconj, chardiv</code>
order of χ	<code>charorder(cyc, χ)</code>
kernel of χ	<code>charker(cyc, χ)</code>
$\chi(x)$, G a GP group structure	<code>chareval($G, \chi, x, \{z\}$)</code>

Dirichlet Characters

initialize $G = (\mathbf{Z}/q\mathbf{Z})^*$	$G = \text{idealstar}(,q)$
is χ odd?	$\text{zncharisodd}(G,\chi)$
real $\chi \rightarrow$ Kronecker symbol $(D/.)$	$\text{znchartokronecker}(G,\chi)$
induce $\chi \in \hat{G}$ to $\mathbf{Z}/N\mathbf{Z}$	$\text{zncharinduce}(G,chi,N)$

Conrey labelling

Conrey label $m \in (\mathbf{Z}/q\mathbf{Z})^* \rightarrow$ character	$\text{znconreychar}(G,m)$
character \rightarrow Conrey label	$\text{znconreyexp}(G,\chi)$
log on Conrey generators	$\text{znconreylog}(G,m)$
conductor of χ (χ_0 primitive)	$\text{znconreyconductor}(G,\chi,\{\chi_0\})$

True-False Tests

is x the disc. of a quadratic field?	$\text{isfundamental}(x)$
is x a prime?	$\text{isprime}(x)$
is x a strong pseudo-prime?	$\text{ispseudoprime}(x)$
is x square-free?	$\text{issquarefree}(x)$
is x a square?	$\text{issquare}(x,\{\&n\})$
is x a perfect power?	$\text{ispower}(x,\{k\},\{\&n\})$
is x a perfect power of a prime? ($x = p^n$)	$\text{isprimepower}(x,\&n\})$
... of a pseudoprime?	$\text{ispseudoprimepower}(x,\&n\})$
is x powerful?	$\text{ispowerful}(x)$
is x a totient? ($x = \varphi(n)$)	$\text{istotient}(x,\{\&n\})$
is x a polygonal number? ($x = P(s,n)$)	$\text{ispolygonal}(x,s,\{\&n\})$
is pol irreducible?	$\text{polisirreducible}(pol)$

Graphic Functions

crude graph of $expr$ between a and b	$\text{plot}(X = a,b,expr)$
High-resolution plot (immediate plot)	
plot $expr$ between a and b	$\text{ploth}(X = a,b,expr,\{flag\},\{n\})$
plot points given by lists lx, ly	$\text{plothraw}(lx,ly,\{flag\})$
terminal dimensions	$\text{plothsizes}()$

Rectwindow functions

init window w , with size x,y	$\text{plotinit}(w,x,y)$
erase window w	$\text{plotkill}(w)$
copy w to w_2 with offset (dx,dy)	$\text{plotcopy}(w,w_2,dx,dy)$
clips contents of w	$\text{plotclip}(w)$
scale coordinates in w	$\text{plotscale}(w,x_1,x_2,y_1,y_2)$
ploth in w	$\text{plotrecth}(w,X = a,b,expr,\{flag\},\{n\})$
plothraw in w	$\text{plotrecthraw}(w,data,\{flag\})$
draw window w_1 at $(x_1,y_1), \dots$	$\text{plotdraw}([[w_1,x_1,y_1],\dots])$

Low-level Rectwindow Functions

set current drawing color in w to c	$\text{plotcolor}(w,c)$
current position of cursor in w	$\text{plotcursor}(w)$
write s at cursor's position	$\text{plotstring}(w,s)$
move cursor to (x,y)	$\text{plotmove}(w,x,y)$
move cursor to $(x+dx,y+dy)$	$\text{plotrmove}(w,dx,dy)$
draw a box to (x_2,y_2)	$\text{plotbox}(w,x_2,y_2)$
draw a box to $(x+dx,y+dy)$	$\text{plotrbox}(w,dx,dy)$
draw polygon	$\text{plotlines}(w,lx,ly,\{flag\})$
draw points	$\text{plotpoints}(w,lx,ly)$
draw line to $(x+dx,y+dy)$	$\text{plotrline}(w,dx,dy)$
draw point $(x+dx,y+dy)$	$\text{plotrpoint}(w,dx,dy)$
draw point $(x+dx,y+dy)$	$\text{plotrpoint}(w,dx,dy)$

Postscript Functions

as ploth	$\text{psploth}(X = a,b,expr,\{flag\},\{n\})$
as plothraw	$\text{psplothraw}(lx,ly,\{flag\})$
as plotdraw	$\text{psdraw}([[w_1,x_1,y_1],\dots])$

Based on an earlier version by Joseph H. Silverman
August 2016 v2.30. Copyright © 2016 K. Belabas
Permission is granted to make and distribute copies of this card provided the
copyright and this permission notice are preserved on all copies.
Send comments and corrections to <Karim.Belabas@math.u-bordeaux.fr>